


SD-49 REV C PG 1



SEE PAGE 14 FOR GASKET INFORMATION.

NO TEST DATA AVAILABLE

PRICING FACTORS 2 1/2" PRESSURE SYSTEM BCE-250



			BCE-25	U		ALOMINOM				
WEIGHT PER FT	EST PER	FACTOR	CAVITY AREA	PART NUMBER	STRUCTURAL VALUES X-X Y-Y	1/8 SIZE DETAILS				
0.109	2.712	25	N/A	BCE5	0.002 I 0.004	Y X F X				
			·		0.006 S 0.009	Y				
2.02=	4= 200	4-			1.935 I 7.802	Y				
2.027	17.289	17	N/A	BCE237	1.548 S 2.297	x) x				
4 (20		1.0	N/A	BCE238	1.102 I 3.249	Y				
1.638	16.567	18			0.882 S 1.351	x x				
1.370	24.887	18	N/A	BCE239	0.770 I 3.037	\mathbf{x}				
1.570	24.007	10	14/21	DCE239	0.529 S 1.219	7 , J				
1.004	11 460	11	27/1	DCE245	0.123 I 0.847	x 🕶 x				
1.004	11.469	11	N/A	BCE245	0.122 S 0.428	Y				
1.504	21.177	1.4	N T / A	DCE246	0.848 I 2.968	x x x				
1.504	21.167	14	N/A	BCE246	0.560 S 1.428	" 1 y"				
1 722	24.940	1.4	N/A	BCE247	1.083 I 5.334	x X X				
1.732		14		BCE247	0.709 S 2.034	T J				
1.072	28.940	15	DT / A	BCE248	1.384 I 8.529	x x x				
1.972		15	N/A		0.926 S 2.750	" L _Y J"				
0.632	9.611	15	N/A	BCE250	0.022 I 0.226	Y X •••• X				
0.032		13			0.040 S 0.181	Y				
0.648	9.599	15	N/A	BCE251	0.023 I 0.280	X Y X				
0.040	9.399	13	14/11	DCE231	0.044 S 0.224	Y				
2.041	17.048	17.040	47.040	47.040	17.049	15	N/A	BCE252	1.593 I 5.492	X X X
2.041	17.046	15	IN/A	DCE252	1.274 S 2.099	Y				
2 221	19.048	19.048 15	N/A	BCE253	1.881 I 8.726	Y X				
2.281					1.505 S 2.807	X X X				
2.254	18.623	18.623 15	N/A	BCE254	1.597 I 7.090	x x				
					1.278 S 2.312	Y				
1.799	15.057	15.057 14	N/A	BCE255	1.303 I 3.105	x x x				
	13.03/	14	IN/A		1.042 S 1.459	Y				
2.339	16.623	12	N/A	BCE256	1.343 I 5.064	X X X				
		10.043	10.023	10.043	14	IN/A	DCE230	1.074 S 2.027	Y	



PRICING FACTORS 2 1/2" PRESSURE SYSTEM BCE-250

SD-49 REV C PG 3

	ALUMINUM				BCE-250	
WEIGHT PER FT	EST PER	FACTOR	CAVITY AREA	PART NUMBER	STRUCTURAL VALUES X-X Y-Y	1/8 SIZE DETAILS
2.975	20.655	12	N/A	BCE257	2.309 I 12.695 1.835 S 3.368	x x
0.186	5.178	28	N/A	BCE258	0.010 I 0.022	Y X X X
0.257	7.394	29	N/A	BCE259	0.016 S 0.034 0.036 I 0.046	x Y x
0.460	7.609	17	N/A	BCE260	0.058 S 0.048 0.009 I 0.262	X Y X Y
0.241	7.720	32	N/A	BCE261	0.021 S 0.220 0.010 I 0.177	X Y X
					0.019 S 0.142 0.012 I 0.187	Y
0.248	7.969	32	N/A	BCE262	0.021 S 0.150 0.841 I 0.724	x X X
0.868	18.294	21	N/A	BCE263	0.673 S 0.398	x x
1.060	22.297	21	N/A	BCE264	1.076 I 1.571 0.861 S 0.673	X X X
0.433	11.849	27	N/A	BCE265	0.088 I 0.381 0.087 S 0.305	x x x
0.872	12.492	14	N/A	BCE266	0.166 I 0.243 0.162 S 0.192	X X X
1.234	16.566	13	N/A	BCE267	0.183 I 1.590 0.139 S 0.751	x 🛂 x
0.121	4.134	34	N/A	BCE268	0.003 I 0.012 0.006 S 0.018	x X X
0.269	5.353	20	N/A	BCE269	0.009 I 0.023 0.018 S 0.046	x L x
0.240	6.894	29	N/A	BCE270	0.033 I 0.036 0.053 S 0.040	x Y x
0.505	13.849	27	N/A	BCE271	0.191 I 0.471 0.149 S 0.377	x = x
1.837	13.008	13	N/A	BCE272	1.421 I 2.862 1.137 S 1.548	x x x

PRICING FACTORS 2 1/2" PRESSURE SYSTEM BCE-250



PG 4			BCE-25	0	•	ALUMINUM						
WEIGHT PER FT	EST PER	FACTOR	CAVITY AREA	PART NUMBER	STRUCTURAL VALUES X-X Y-Y	1/8 SIZE DETAILS						
	4.4.000	45		D.CEO.	1.500 I 3.868	У						
1.669	14.330	17	N/A	BCE273	1.200 S 1.685	X X Y						
2.156	16.588	1.5	N/A	D.CE074	1.870 I 7.680	x X						
	10.500	15	IN/A	BCE274	1.496 S 2.724	Y						
3.988	23.093	10	N/A	BCE275	3.189 I 22.300	x x						
	23.073	10	14/11		2.551 S 5.574	Y						
0.872	9.957	22	N/A	BCE276	0.713 I 0.713	x						
	J.557	22	14/11	DGEZTO	0.570 S 0.570	Y						
0.344	9.427	27	N/A	BCE277	0.039 I 0.281	Y						
	J. 12 /	2,	14/11	DCEZ	0.048 S 0.225	x x						
0.564	15.846	28	N/A	BCE278	0.340 I 0.524	x x						
	13.010	20	11/21	DCE2/0	0.217 S 0.419	Y						
0.582	15.500	27	N/A	BCE279	0.289 I 0.548	x dx						
				2 322/3	0.204 S 0.438	Y						
2.035	18.753	9	9 N/A	BCE280	0.734 I 2.741	x X						
			- ',		0.656 S 1.728	Y T						
2.413	20.403	8	N/A	BCE281	0.799 I 5.913	x X						
			,		0.714 S 2.798	Y J						
2.518	22.083	9	N/A	BCE282	0.752 I 9.297	x X						
-									0.687 S 3.587	_ Y		
1.462	26.387	26.387	26.387	26.387	26.387	26.387	26.387	18	N/A	BCE283	0.943 I 0.872	x F x
			,		0.750 S 0.466	Y						
0.592	10.761	10.761	10.761	10.761	18	N/A	BCE284	0.035 I 0.347	$x \stackrel{Y}{\swarrow} x$			
					0.054 S 0.241							
0.524	14.461	28	N/A	BCE285	0.134 I 0.528	\mathbf{x} \mathbf{y} \mathbf{y} \mathbf{x}						
					0.113 S 0.352	Y Y						
0.924	19.847	21	N/A	BCE286	0.295 I 0.599	x						
					0.214 S 0.479	Y						
0.451	12.349	12.349 27	N/A	BCE287	0.109 I 0.404	x x						
					ŕ		0.101 S 0.323	Y				



PRICING FACTORS 2 1/2" PRESSURE SYSTEM BCE-250

SD-49 REV C PG 5

Description Performance Performance		LOMINOM				DCE-230				
0.589		EST PER	FACTOR			STRUCTURAL VALUES X-X Y-Y	1/8 SIZE DETAILS			
0.329 6.882 21 N/A BCE289 0.007 I 0.189	0.589	15.703	27	N/A	BCE288	0.309 I 0.558	x x			
1.240	0.329	6.882	21	N/A	BCE289	0.007 I 0.189	=			
0.563										
0.646 10.677 17 N/A BCE295 0.134 I 0.418	1.240	22.892	18	N/A	BCE290	0.648 S 0.336	生			
0.646 10.677 17 N/A BCE295 0.134 I 0.418	0.563	9.303	17	N/A	BCE294		x X			
0.604 9.917 16 N/A BCE296 0.114 1 0.359 Y X X X X X X X X X X X X X X X X X X							Y			
0.604 9.917 16 N/A BCE296 0.114 1 0.339 1.536 22.508 15 N/A BCE298 0.644 I 2.045 0.430 S 1.055 0.229 5.893 26 N/A BCE299 0.001 I 0.107 0.003 S 0.095 1.492 27.107 18 N/A BCE2537 0.160 I 10.476 0.166 S 2.174 0.166 S 2.174 0.283 S 2.373 1.565 25.960 17 N/A BCE2538 0.283 S 2.373 0.283 S 2.373 4.794 30.915 6 N/A BCE2550 0.176 I 3.883 0.283 S 2.373 1.078 18.762 17 N/A BCE2552 0.176 I 3.883 0.138 S 1.238 0.138 S 1.238 1.184 19.450 16 N/A BCE2553 0.263 I 4.441 0.29 0.283 S 2.373 0.338 6.763 20 N/A BCE2556 0.003 I 0.129 0.009 S 0.116 0.009 S 0.116 0.168 6.039 36 N/A BCE2557 0.004 I 0.089 0.009 S 0.116	0.646	10.677	17	N/A	BCE295	0.110 S 0.273	x x			
1.536	0.604	9.917	16	N/A	BCE296	0.114 I 0.359	ſ			
1.536										
0.229 5.893 26 N/A BCE299 0.003 S 0.095 X X X X 1.492 27.107 18 N/A BCE2537 0.160 I 10.476 X X X X 1.565 25.960 17 N/A BCE2538 0.393 I 11.429 Y X X X X </td <td>1.536</td> <td>22.508</td> <td>15</td> <td>N/A</td> <td>BCE298</td> <td></td> <td>x = x</td>	1.536	22.508	15	N/A	BCE298		x = x			
1.492 27.107 18 N/A BCE2537 0.160 I 10.476 0.166 S 2.174 X X X X X X X X X X X X X X X X X X X	0.229	5 803	26	NT / A	PCE200	0.001 I 0.107	Y			
1.492 27.107 18		3.073	20	14/11	DCE277		X X X			
1.565	1.492	27.107	18	N/A	BCE2537		x X			
4.794 30.915 6 N/A BCE2550 9.174 I 8.210 x	1 565	25 960	17	N/A	BCF2538	0.393 I 11.429	Y			
4.794 30.915 6 N/A BCE2550 2.458 S 2.737 1.078 18.762 17 N/A BCE2552 0.176 I 3.883		23.700	1	14/11	BGI2330	0.283 S 2.373	x x			
2.458 S 2.737 1.078 18.762 17 N/A BCE2552 0.176 I 3.883 0.138 S 1.238 1.184 19.450 16 N/A BCE2553 0.263 I 4.441 0.247 S 1.326 0.338 6.763 20 N/A BCE2556 0.003 I 0.129 0.009 S 0.116 0.168 6.039 36 N/A BCE2557 0.004 I 0.089	4 794	30 915	30.015	30 015	30.015	6	N/A	BCF2550	9.174 I 8.210	x x
1.078	1.771	30.713	U	14/11	BCII233 0	2.458 S 2.737	Y			
1.184 19.450 16 N/A BCE2553 0.263 I 4.441 Y X X X X X X X X X X X X X X X X X X	1.078	18.762	17	N/A	BCE2552	0.176 I 3.883	1 L			
1.184							Y			
0.338 6.763 20 N/A BCE2556 0.009 S 0.116 X Y X X X X X X X X X X X X X X X X X	1.184	19.450	16	N/A	BCE2553		X			
0.009 S 0.116 0.168 6.039 36 N/A BCE2557 0.004 I 0.089 X X X	0 338	6 762	63 20	N/A	BCE2556	0.003 I 0.129	x Y x			
0.168 6.039 36 N/A BCE2557 x x		0.703	20	11/11	2012330					
	0.168	6.039	36	N/A	BCE2557	0.004 1 0.089 0.012 S 0.071	$x \stackrel{Y}{\underbrace{\hspace{1cm}}} x$			


PRICING FACTORS 2 1/2" PRESSURE SYSTEM BCE 250



PG 0			BCE-25	0		ALUMINUM
WEIGHT PER FT	EST PER	FACTOR	CAVITY AREA	PART NUMBER	STRUCTURAL VALUES X-X Y-Y	1/8 SIZE DETAILS
0.436	9.872	23	N/A	BCE2558	0.022 I 0.277 0.033 S 0.221	x Y x
0.397	6.986	18	N/A	BCE2560	0.003 I 0.207	X Y X
0.264	8.415	32	N/A	BCE2561	0.009 S 0.174 0.010 I 0.200 0.019 S 0.160	x Y x
0.271	8.664	32	N/A	BCE2562	0.019 S 0.160 0.012 I 0.208 0.022 S 0.166	x Y X
0.220	6.975	32	N/A	BCE2563	0.004 I 0.150 0.010 S 0.120	x Y x
0.234	7.481	32	N/A	BCE2564	0.016 S 0.126 0.007 I 0.168 0.015 S 0.134	x Y X
0.449	11.197	25	N/A	BCE2565	0.121 I 0.364 0.117 S 0.291	x V x
1.308	17.570	13	N/A	BCE2567	0.117 S 0.291 0.189 I 2.149 0.141 S 0.884	x Y x
2.002	34.355	17	N/A	BCE2575	1.686 I 6.835 1.349 S 1.743	Y X
1.267	25.387	20	N/A	BCE2576	1.345 I 2.731 1.076 S 0.930	X X
0.304	7.012	23	N/A	BCE492	0.001 I 0.201	Y X Y X
0.370	8.473	23	N/A	BCE475	0.004 S 0.141 0.001 I 0.356 0.003 S 0.204	$X \xrightarrow{Y} X$
0.600	8.229	14	N/A	A1253	0.003 S 0.204 0.045 I 0.366 0.063 S 0.325	x Y x
0.852	11.579	14	N/A	BCE212	0.067 I 0.896 0.079 S 0.382	$x \stackrel{Y}{\bigsqcup_{Y}} x$
1.224	15.282	12	N/A	BCE2570	0.257 I 0.676 0.317 S 0.601	x X X
2.057	15.008	14	N/A	BCE2573	1.714 I 5.065 1.371 S 2.231	X X X
	L		L		<u>l</u>	1

WINDLOAD CHARTS 2 1/2" PRESSURE SYSTEM BCE-250

SD-49 REV C PG 7




#1 THESE WINDLOAD CHARTS ARE BASED UPON THE LESSER OF DEFLECTION RATIO (L/175) OR STRESS (12667)

#2 THESE STRUCTURAL CURVES ARE ESTIMATES AND ARE PRESENTED TO THE BEST KNOWLEDGE OF THE WILLIAM L BONNELL CO. IT IS, HOWEVER, THE RESPONSIBILITY OF THE CUSTOMER TO BE SATISFIED THAT THE CURVES ARE CORRECT. THE WILLIAM L BONNELL CO. MAY NOT BE HELD RESPONSIBLE IN ANY WAY FOR THE FAILURE OF PERFORMANCE RESULTING FROM THE USE OF THESE CURVES.


WINDLOAD CHARTS 2 1/2" PRESSURE SYSTEM BCE-250





WINDLOAD CHARTS 2 1/2" PRESSURE SYSTEM BCE-250


SD-49 REV C PG 9




^{#1} THESE WINDLOAD CHARTS ARE BASED UPON THE LESSER OF DEFLECTION RATIO (L/175) OR STRESS (12667)

WINDLOAD CHARTS 2 1/2" PRESSURE SYSTEM BCE-250








#1 THESE WINDLOAD CHARTS ARE BASED UPON THE LESSER OF DEFLECTION RATIO (L/175) OR STRESS (12667)

#2 THESE STRUCTURAL CURVES ARE ESTIMATES AND ARE PRESENTED TO THE BEST KNOWLEDGE OF THE WILLIAM L BONNELL CO. IT IS, HOWEVER, THE RESPONSIBILITY OF THE CUSTOMER TO BE SATISFIED THAT THE CURVES ARE CORRECT. THE WILLIAM L BONNELL CO. MAY NOT BE HELD RESPONSIBLE IN ANY WAY FOR THE FAILURE OF PERFORMANCE RESULTING FROM THE USE OF THESE CURVES.

WINDLOAD CHARTS 2 1/2" PRESSURE SYSTEM BCE-250


SD-49 REV C PG 11



^{#1} THESE WINDLOAD CHARTS ARE BASED UPON THE LESSER OF DEFLECTION RATIO (L/175) OR STRESS (12667)

WINDLOAD CHARTS 2 1/2" PRESSURE SYSTEM BCE-250






#2 THESE STRUCTURAL CURVES ARE ESTIMATES AND ARE PRESENTED TO THE BEST KNOWLEDGE OF THE WILLIAM L BONNELL CO. IT IS, HOWEVER, THE RESPONSIBILITY OF THE CUSTOMER TO BE SATISFIED THAT THE CURVES ARE CORRECT. THE WILLIAM L BONNELL CO. MAY NOT BE HELD RESPONSIBLE IN ANY WAY FOR THE FAILURE OF PERFORMANCE RESULTING FROM THE USE OF THESE CURVES.

WINDLOAD CHARTS 2 1/2" PRESSURE SYSTEM BCE-250

SD-49 REV C PG 13



#1 THESE WINDLOAD CHARTS ARE BASED UPON THE LESSER OF DEFLECTION RATIO (L/175) OR STRESS (12667)

#2 THESE STRUCTURAL CURVES ARE ESTIMATES AND ARE PRESENTED TO THE BEST KNOWLEDGE OF THE WILLIAM L BONNELL CO. IT IS, HOWEVER, THE RESPONSIBILITY OF THE CUSTOMER TO BE SATISFIED THAT THE CURVES ARE CORRECT. THE WILLIAM L BONNELL CO. MAY NOT BE HELD RESPONSIBLE IN ANY WAY FOR THE FAILURE OF PERFORMANCE RESULTING FROM THE USE OF THESE CURVES.

GASKET INFORMATION 2 1/2" PRESSURE SYSTEM BCE-250 SERIES



FASTENERS

- 1. SHEAR BLOCK ATTACHMENTS ARE INTENDED TO BE SECURED WITH #10 SCREWS
- 2. PRESSURE PLATE ATTACHMENTS ARE DESIGNED TO BE SECURED WITH 1/4"-20 MACHINE SCREWS, 9" ON CENTER.

 SCREWS OF MOST ASSEMBLYS ACCEPT 1/4"-20 x 3/4" LONG. CHECK YOUR COMBINATION TO CONFIRM YOUR REQUIREMENTS.
 - *NOTE REGARDING CORNER EXTENSIONS BCE-283, -286, & -290, SCREW LENGTHS VARY DEPENDING ON USAGE, CHECK YOUR APPLICATION FOR REQUIRED LENGTH AND THREAD TYPE.
- 3. ANCHOR BOLTS SHOULD BE SIZED ACCORDING TO LOAD REQUIREMENTS.

	GASKETS	
UNIVERSAL RUBBER CO. 800-782-2375	#2272 #2337 #2148 #2338	SPONGE GLAZING GASKET EXTERIOR SPONGE GLAZING GASKET EXTERIOR SPONGE GLAZING GASKET EXTERIOR HARD GLAZING GASKET INTERIOR
REED RUBBER PRODUCTS 800-325-9698	#B-115 #B-116 #B-140	SPONGE GASKET INTERIOR HARD GASKET EXTERIOR SPONGE GLAZING GASKET INTERIOR AND EXTERIOR
TREMCO 800-321-6357	#TR-647E #TR-646N	EXTERIOR GLAZING GASKET INTERIOR GLAZING GASKET
,	THERMAL ISOLATO	OR .
REBCO INC. 973-684-0200	#42-802	PRESSURE PLATE RIGID VINYL
LOXCREEN COMPANY 912-842-2439	#V-5374	PRESSURE PLATE RIGID VINYL
	DOOR PILE	
SCHLEGEL CORP. 800-828-6237	AS SELECTED	USED WITH BCE-5
AMESBURY GROUP INC. 704-878-6892	AS SELECTED	USED WITH BCE-5

END DAMS FOR HORIZONTALS

WHEN THIS SYSTEM IS USED IN HIGH APPLICATIONS, END DAMS ARE BENEFICIAL TO FORCE INFILTRATED MOISTURE OUT THRU WEEP HOLES IN THE HORIZONTAL PRESSURE PLATES.

A SECOND POINT OF CONCERN INVOLVES CLOSING THE ENDS OF THE GLASS SUPPORT TONGUE (SUCH AS ON BCE-239 & BCE-2575) THAT CREATES AN OPENING FROM THE GLASS POCKET TO THE INTERIOR OF THE HORIZONTAL TUBE CAVITY TO PREVENT INFILTRATED MOISTURE MIGRATING FROM THE GLASS POCKET INTO THE CAVITY.

CLOSED CELL SPONGE IS ORDERED BY SPECIFYING DIMENSIONS AND CAN BE ORDERED WITH OR WITHOUT ADHESIVE.


SEALING AROUND PLUGS TO CLOSE VOIDS MAY BE REQUIRED.


1.500 X 1.125 X .500 THK. FOR 1" GLASS .750 X 1.125 X .500 THK. FOR 1/4" GLASS

SECON RUBBER AND PLASTICS INC. MAT'L: NBR/PVC BLEND


618-282-7700


SD-49 REV C PG 15





* RIGID VINYL SEPARATOR SPECIFY SEPERATELY






DETAIL SHEET 2 1/2" PRESSURE SYSTEM BCE-250



 $5\frac{1}{2}$


 $\frac{21}{32}$


FULL SIZE DETAILS



* RIGID VINYL SEPARATOR SPECIFY SEPERATELY

SD-49 REV C PG 17







* RIGID VINYL SEPARATOR SPECIFY SEPERATELY


DETAIL SHEET 2 1/2" PRESSURE SYSTEM BCE-250







SD-49 REV C PG 19












DETAIL SHEET 2 1/2" PRESSURE SYSTEM BCE-250









SD-49 REV C PG 21





DETAIL SHEET 2 1/2" PRESSURE SYSTEM BCE-250













* RIGID VINYL SEPARATOR SPECIFY SEPERATELY









* RIGID VINYL SEPARATOR SPECIFY SEPERATELY

BCE-250

FULL SIZE DETAILS


* RIGID VINYL SEPARATOR SPECIFY SEPERATELY





DETAIL SHEET 2 1/2" PRESSURE SYSTEM BCE-250





SD-49 REV C PG 27

